

TRACKER 2



1652001 • Clear Lens



1652002 • Smoke Lens



1652010 • Twilight Lens



1652007 • Polarised Lens



Accessories:
1652015 • Rx Adaptor

Tracker 2 Welding also available:
1652016 • Shade 3
1652017 • Shade 5







50 g

- + CAN BE FITTED WITH AN RX PRESCRIPTION LENS**
- + 8 BASE CURVE**
- + RUBBERISED EYE SEAL PROVIDES EXCEPTIONAL PROTECTION AGAINST DUST AND OTHER PARTICLES**
- + ADJUSTABLE HEAD STRAP**

bolle
SAFETY

TRACKER 2

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
TRACKER 2	 Clear	1652001	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1652002	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Twilight	1652010	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Grey Polarised	1652007	I2	AS/NZS 1337.1.2010	Hardcoat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 2. Range of luminous transmittance 18-43% (flash & polarised).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Dust protection
- Engineering/process work
- Solar UV exposure
- Milling
- Rigging
- Laboratory work

MAIN MARKETS

- Mining
- Manufacturing
- Construction
- Local Government/Councils
- Utilities: power, gas and water boards
- Petro Chemical

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lenses: Clear, Smoke and Twilight
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Twilight and Polarised

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s. Meets the requirements of splash approval when used with the supplied head strap correctly adjusted.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz