

# PILOT 2

FIRE  
FIGHTING  
GOGGLE

ADVANCED TECHNOLOGY FOR FIRE FIGHTING

Pilot 2 is designed to fit comfortably under fire fighter helmets.  
Pilot 2 Fire's co-injected frame guarantees unequalled adaptability and comfort.

 PLATINUM




TEMPERATURE  
RESISTANCE  
tested at 200°C

- ✓ Frame
- ✓ Lens
- ✓ Strap



1689119 • Platinum  
Clear Lens

  
87 g

- + DESIGNED TO FIT COMFORTABLY UNDER FIRE FIGHTING HELMETS
- +  PLATINUM COATING (P)
- + ADJUSTABLE STRAP
- + FITS OVER PRESCRIPTION GLASSES


- + EXCELLENT FIELD OF VISION
- + PP/TPR TWO-MATERIAL FRAME

**bolle**  
SAFETY

# PILOT 2

## FIRE FIGHTING GOGGLE

### ADVANCED TECHNOLOGY FOR FIRE FIGHTING

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>PILOT 2</b>	 Clear	1689119	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (†P)

#### LENS MARKING

- †P. Platinum is a permanent coating on both sides of the lens giving them a high resistance to scratching (1.4 cd / m<sup>2</sup>), to the most aggressive chemicals and delays the onset of fogging as per the testing requirements of EN166.
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

#### OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).

#### TECHNOLOGIES

##### PLATINUM

The new exclusive scratch and fog resistant coating K and N certified PLATINUM guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

#### LENS

- 2 mm polycarbonate
- Platinum anti-fog/anti-scratch coating coating on both sides of lens.
- 100% UV385: Clear

#### FRAME MARKING

**AS/NZS 1337.1.2010:** Tested and approved to. AS/NZS 1337.1.2010 - Medium Impact protection & Chemical splash

#### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

#### CHARACTERISTICS

LENSES	PC - 2,1 mm - Curve 5,5
FRAME	PP + TPR
TEMPLES	Non applicable
STRAP	Nylon
FOAM	No
SPARE LENSES	No

08/06/2018

#### ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

#### NEW ZEALAND:

T.: 0800 2655 369  
E: bolle@bolle.co.nz