

IRI-S DIOPTER

IRI-S, A SINGLE MODEL FOR THOUSANDS OF FACES

IRI-S, the first universal safety spectacle that fits perfectly to every face. Featuring a B-Flex nose bridge, fully adjustable in height, depth and width. An ultra-lightweight frame with pivoting ergonomic temples, fitting precisely to all face shapes and features five reading area diopter versions.



Smoke Lens
+1.0 : IRIDPSF1
+1.5 : IRIDPSF1.5
+2.0 : IRIDPSF2
+2.5 : IRIDPSF2.5
+3.0 : IRIDPSF3



27 g



Multi adjustable
B-Flex nose bridge
allows tilt and
width adjustability



Tilt adjustable,
co-moulded
temple arms for
customised
secure fit





Clear Lens
+1.0 : 1671001
+1.5 : 1671002
+2.0 : 1671003
+2.5 : 1671004
+3.0 : 1671005

- + 1 MODEL – 1 SIZE**
- + TILT ADJUSTABLE, CO-MOULDED TEMPLE ARMS**
- + 5 DIOPTER READING OPTIONS**
- + MULTI ADJUSTABLE **B**FLEX NOSE BRIDGE**
- + UNISEX FIT – MEDIUM / LARGE**

bolle
SAFETY

IRI-S DIOPTER

IRI-S, A SINGLE MODEL FOR THOUSANDS OF FACES

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS	
IRI-S DIOPTER		Clear Lens +1.0	1671001	IO	ATS105.1.2016	Anti-scratch/Anti-fog
		Clear Lens +1.5	1671002	IO	ATS105.1.2016	Anti-scratch/Anti-fog
		Clear Lens +2.0	1671003	IO	ATS105.1.2016	Anti-scratch/Anti-fog
		Clear Lens +2.5	1671004	IO	ATS105.1.2016	Anti-scratch/Anti-fog
		Clear Lens +3.0	1671005	IO	ATS105.1.2016	Anti-scratch/Anti-fog
		Smoke Lens +1.0	IRIDPSF1	I3	ATS105.1.2016	Anti-scratch/Anti-fog
		Smoke Lens +1.5	IRIDPSF1.5	I3	ATS105.1.2016	Anti-scratch/Anti-fog
		Smoke Lens +2.0	IRIDPSF2	I3	ATS105.1.2016	Anti-scratch/Anti-fog
		Smoke Lens +2.5	IRIDPSF2.5	I3	ATS105.1.2016	Anti-scratch/Anti-fog
		Smoke Lens +3.0	IRIDPSF3	I3	ATS105.1.2016	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (Clear).
- 3. Range of luminous transmittance 8 -18% (Smoke).


APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory
- Dental

MAIN MARKETS

- Manufacturing
- Local government and councils
- Utilities: power, gas, water and roads
- Medical and dental
- Transport
- Mining
- Construction

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our  cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 10
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

11/07/2018

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY