

COBRA TPR

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

With its easy-to-clean neoprene strap and its built-in TPR foam, this goggle kit is especially suitable for clean industries and the agro-food industry.

 PLATINUM®



1667001 • Clear with Neoprene Strap



1667101 • Clear



1667102 • Smoke






34g

- +  PLATINUM® (+P) COATING
- + COMPACT, LIGHTWEIGHT AND PANORAMIC
- + NEOPRENE STRAP AND COMFORT FOAM
- + 100% SEALED
- + HIGH STRENGTH GOGGLES

bolle
SAFETY

COBRA TPR

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
COBRA TPR	 Clear with Neoprene Strap	1667001	IO & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/P
	 Clear	1667101	IO & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/P
	 Smoke	1667102	11 & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/P

LENS MARKING

- P.** Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- I.** The letter 'I' signifies 'Medium Impact' approval.
- O.** The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- O.** Range of luminous transmittance 80–100% (Clear).
- 3.** Range of luminous transmittance 8–18% (Smoke).

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

APPLICATIONS

- Cutting
- Spraying
- Dust protection

MAIN MARKETS

- Construction
- Manufacturing
- Paint
- Automotive

LENSES

- Platinum Coating - A high performance anti-fog + anti-scratch coating system applied on both sides of Clear and Smoke lenses
- 2mm polycarbonate
- 9 base curve
- 100% UV 385 – Clear

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40°, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	Non Applicable
STRAP	15mm adjustable
FOAM	TPR
SPARE LENSES	No

TECHNOLOGIES



The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

02/11/2018

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY