

PILOT 2 NEO

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Its co-injected, vented frame guarantees unequalled adaptability and comfort while the neoprene strap improves resistance to temperature, fire, tearing and chemical products. PILOT 2 NEO is perfectly adapted to oil and gas environments.

 PLATINUM



PSGPIL2-L17



PSGPIL2-L16






89 g

- + EXCELLENT FIELD OF VISION**
- + PP/TPR TWIN-MATERIAL FRAME**
- +  PLATINUM COATING (P)**
- + ADJUSTABLE NEOPRENE STRAP**
- + FITS OVER PRESCRIPTION GLASSES**

bolle
SAFETY

PILOT 2 NEO

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PILOT 2 NEO	 Clear Vented	PSGPIL2-L16	 CIO	AS/NZS 1337.1:2010	Anti-scratch/anti-fog (PF)
	 CSP Vented	PSGPIL2-L17	 CI1	AS/NZS 1337.1:2010	Anti-scratch/anti-fog (PF)

LENS MARKING

PF. Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

- C. The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical handling.
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

Ocular lens category:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 - 88% (CSP).

Others symbols:

 Manufacturer name

TECHNOLOGIES

CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM coating that sustainably combats fogging.

PLATINUM

The exclusive scratch and fog resistant coating K and N certified PLATINUM guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

PACKAGING AND GTIN		
	PSGPIL2-L16	PSGPIL2-L17
Individual plastic bag	9318330048571	9318330048588
5 safety goggles per inner box	(01)19318330048578	(01)19318330048585
80 safety goggles per outer pack	(01)29318330048575	(01)29318330048582



Bollé Safety AU Pty Limited
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bollesafety.com.au

LENSES

- Platinum Coating - a high performance anti-fog + anti-scratch coating system applied on both sides of Clear and CSP lenses
- 99.99% UV 385 - Clear
- 99.99% UV 400 - CSP

FRAME MARKING

AS/NZS 1337.1:2010 Tested and approved to AS/NZS 1337.1:2010 for medium impact and chemical splash protection. Resists a 6mm ball at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS	
LENSES	PC - 2,1 mm - Curve 5,5
FRAME	PP + TPR
TEMPLES	Non applicable
STRAP	Neoprene
FOAM	No
SPARE LENSES	No

Non-contractual pictures

10/02/2021

bolle
SAFETY