

RUSH+

FOR HEALTHCARE PROFESSIONALS

This advanced eye protection was specifically designed for healthcare professionals; its design combines ultimate protection and comfort to help reduce workplace accidents. Equipped with **Platinum® anti-scratch and anti-fog coating** on both sides of the lens, RUSH+ ensures long-lasting comfort, performance and reliability.



Non-slip
adjustable bridge

RUSH+ is customized for:
lens marking, colored temples...

Information & conditions : marketing@bolle-safety.com

26 g

- + UPPER PROTECTION**
- + PLATINUM® ANTI-FOG & ANTI-SCRATCH COATING (+P)**
- + CO-INJECTED, ULTRA-FLEX TEMPLES**
- + NON-SLIP ADJUSTABLE BRIDGE**
- + WASHABLE AND REUSABLE**

bolle
SAFETY

RUSH+

FOR HEALTHCARE PROFESSIONALS

MODEL	VERSIONS	REFERENCES	LENS MARKINGS			FRAME MARKINGS			COATINGS
			EN166	ANSI	AS/NZS	EN166	ANSI	AS/NZS	
RUSH+	Clear	PSSRUSP085	ZC-1.2 1 FT KN CE	Z87+ U6	IO	EN166 FT CE	Z87+	AS/NZS 1337.1	Anti-scratch/Anti-fog

LENS MARKING

Manufacturer name

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

CE European standard

Z87+ = Impact rated for Plano product
Tested and approved to ANSI Z81.1-2015

Lens type

- Clear = none
- Welding = W and scale number from 1.3 to 14
- UV filter = U and scale number from 2 to 6
- Visible light filter = L and scale number from 1.3 to 10
- IR filter = R and scale number from 1.3 to 10
- Variable tint = V
- Special purpose = S

O. Range of luminous transmittance 80-100% (clear)

FRAME MARKING

Manufacturer name

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorizes use for high speed particles at extreme temperatures.

CE European standard

Z87+ = Impact rated for Plano product
Tested and approved to ANSI Z81.1-2015

Country of origin: Taiwan

ANSI: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Maximum protection for glasses. Use for high speed particles at extreme temperatures.

AS/NZS 1337.1:2010 : Tested & approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

Bollé Safety product approval certificates to standards will be sent on request.

TECHNOLOGIES

PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the glasses or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	-
TEMPLES	PC + TPR
SPARE LENSES	No

PACKAGING AND EAN13 CODE	
	PSSRUSP085
Individual plastic bag	3660740013042
10 safety glasses per inner box	3660740113049
200 safety glasses per outer pack	3660740213046

27/07/2021

Europe Bollé Safety
34 Rue de la Soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
e-mail : advfrance@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead
Road - Chessington Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

APAC
Bollé Safety AU Pty Limited
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

bolle-safety.com

bolle
SAFETY